

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/077565 A1

(51) International Patent Classification⁷: **B21J 5/02**

(21) International Application Number:
PCT/NO2005/000054

(22) International Filing Date: 14 February 2005 (14.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20040634 12 February 2004 (12.02.2004) NO

(71) Applicant (for all designated States except US): RAU-
FOSS TECHNOLOGY AS [NO/NO]; Boks 77, N-2831
Raufoss (NO).

(72) Inventor; and

(75) Inventor/Applicant (for US only): RUSTE, Trygve
[NO/NO]; Østveien 12, N-2830 Raufoss (NO).

(74) Agent: OSLO PATENTKONTOR AS; Postboks 7007 M,
N-0306 Oslo (NO).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: A METHOD AND TOOL FOR CLOSED DIE FORGING



(57) Abstract: A press tool for closed die forging a blank into a product is described. Said tool including upper and lower centre members 21, 22 and first (23, 24) and second (25, 26) side members. Said members define a cavity with the form of the product. In a two-step closed die forge process the blank 20 is placed between said upper and lower centre members 21, 22. The first (23, 24) and second (25, 26) side members are forced against the blank 20 horizontally upsetting the outer edges of the blank. Then, the centre members are forced vertically into the blank, until the material in the blank has substantially filled the cavity.

BEST AVAILABLE COPY

WO 2005/077565 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.